

螺栓系列



BOLT SERIES

外六角螺丝



DIN933 全牙

材质: 304、316、2205、316L、2507、
304Pro(低磁)
直径: M3-M64 长度: 6-300
牙别: 全牙、粗牙



DIN931 半牙

材质: 304、316、2205、2507、309
304Pro(低磁)
直径: M6-M64 长度: 30-350
牙别: 半牙



GB5783 全牙

材质: 304、316、2205、316L、2507
304Pro(低磁)
直径: M10、M12 长度: 16-300
牙别: 全牙



GB5782 半牙

材质: 304、316、2205、2507、304Pro(低磁)
直径: M10、M12 长度: 35-300
牙别: 半牙



GB30 14P

材质: 304、316、2507、304Pro(低磁)
直径: M8 长度: 12-200
牙别: 全牙



ANSIB18.2.1 美标

材质: 304、316、2507、304Pro(低磁)
直径: 1/4-1 长度: 3/8-12
牙别: 全牙、半牙



JISB1180 日标螺丝

材质: 304、316、2507、304Pro(低磁)
直径: M5-M20 长度: 10-300
牙别: 全牙、半牙

马车(方颈)螺栓



DIN603 大头

材质: 304,316
直径: M5-M16 长度: 12-200
牙别: 全牙



GB12 小头

材质: 304,316
直径: M5-M16 长度: 16-200
牙别: 全牙



ANSIB18.5 马车

材质: 304,316
直径: 1/4-1/2 长度: 1/2-6
牙别: 全牙

法兰螺栓



GB5787 带齿

材质: 304,316
直径: M5-M12 长度: 10-150



GB5789 加大带齿

材质: 304,316
直径: M5-M12 长度: 10-150



ANSIB18.2.1 平脑、凹脑

材质: 304,316
直径: 1/4-3/8 长度: 3/4-2"
牙别: 粗牙

T型螺栓



GB37 槽用

材质: 304,316
直径: M5-M12 长度: 12-70
牙别: 全牙



光伏用T型螺栓

材质: 304,316 直径: M8
长度: 20-70 牙别: 粗牙
规格: 14.5x8x5, 18x8x5, 23x10x4



预埋T型栓 30/20型平齿

材质: 304
直径: M12 长度: 50
牙别: 全牙



预埋T型栓 38/23型平齿

材质: 304
直径: M12 M16 长度: 50
牙别: 全牙



欧标T型螺栓 20型

材质: 304
直径: M5 长度: 40
牙别: 全牙



欧标T型螺栓 30型

材质: 304
直径: M6 长度: 40
牙别: 全牙



欧标T型螺栓 40型

材质: 304
直径: M8 长度: 40
牙别: 全牙



欧标T型螺栓 45型

材质: 304
直径: M8 长度: 40
牙别: 全牙

方头螺栓



GB35

材质: 304,316
直径: M5-M12 长度: 12-60
牙别: 粗牙



地脚螺栓

材质: 304
直径: M16-M30
长度: 300-500



NUT SERIES

六角螺帽



DIN934

材质: 304,316,2205,2507
直径: M1.6-M64
牙别: 不攻牙、攻左牙、粗牙、细牙
极细牙、特细牙



DIN439 薄型

材质: 304,316
直径: M6-M24
牙别: 粗牙



GB6170

材质: 304,316,2205,2507
直径: M5-M39
牙别: 不攻牙、攻左牙、粗牙



GB52 14P

材质: 304,316
直径: M8
牙别: 粗牙



GB6172 薄型

材质: 304,316
直径: M2-M48
牙别: 不攻牙、粗牙



GB6175 加厚

材质: 304,316,2205,2507
直径: M8-M48
牙别: 粗牙



ANSI B18.6.3 机螺帽

材质: 304,316
直径: 8#,10#
牙别: 粗牙、细牙



ANSI B18.2.2 美标细牙

材质: 304,316
直径: 3/16-1
牙别: 细牙



ANSI B18.2.2 美标粗牙

材质: 304,316
直径: 3/16-1
牙别: 粗牙



ANSIB18.2.2 薄型

材质: 304,316
直径: 1/4-1
牙别: 粗牙、细牙



台规惠氏螺帽

材质: 304,316
直径: 1/4-5/8
牙别: 惠氏牙



GB6171 细牙

材质: 304,316
直径: M8-M20
牙别: 细牙、极细牙、特细牙



JISB1181 六角帽

材质: 304,316,TW340日本钛合金
直径: M3-M22
牙别: 粗牙



GB6173 细牙

材质: 304,316
直径: M6-M20
牙别: 细牙、极细牙、特细牙



塑料外六角螺帽 似DIN934

材质: 尼龙(PA66)、聚丙烯(PP)、聚氯乙烯(PVC)
直径: M3-M24
牙别: 粗牙

锁紧防松螺帽



DIN985

材质: 304,316
直径: M3-M36
牙别: 粗牙、细牙、特细牙



DIN982 加厚

材质: 304,316
直径: M4-M20
牙别: 粗牙



DIN986 盖式

材质: 304
直径: M4-M12
牙别: 粗牙



GB889.1 非金属镶嵌六角螺帽

材质: 316
直径: M10-M12
牙别: 粗牙



DIN980V 压点式

材质: 304
直径: M6-M12
牙别: 粗牙



美标尼龙锁紧

材质: 304,316
直径: 1/4-3/4
牙别: 粗牙



DIN980M 国产金属锁紧

材质: 304
直径: M5-M16
牙别: 粗牙



DIN980M 进口金属锁紧

材质: 304
直径: M5-M20
牙别: 粗牙



GB6184 金属锁紧

材质: 304
直径: M3-M20
牙别: 粗牙

盖型螺帽



DIN1587

材质: 304,316
直径: M3-M48
牙别: 粗牙、细牙、特细牙



IFI 美标盖帽

材质: 304,316
直径: 10#-3/4
牙别: 粗牙



DIN917

材质: 304
直径: M3-M12
牙别: 粗牙

法兰螺帽



DIN6923 带齿

材质: 304,316
直径: M3-M16
牙别: 粗牙



DIN6926 尼龙

材质: 304,316
直径: M4-M10
牙别: 粗牙



IFI145

材质: 304,316
直径: 1/4-1/2
牙别: 粗牙

花色螺帽



DIN557 四方

材质: 304,316
直径: M3-M12
牙别: 粗牙



DIN928 四方

材质: 304,316
直径: M4-M10
牙别: 粗牙



DIN929 六角

材质: 304,316
直径: M4-M12
牙别: 粗牙



K帽

材质: 304+420
直径: M3-M10
牙别: 粗牙



DIN6334 六角长螺母(进口)

材质: 304,316
直径: M5-M16



DIN7967 紧扣螺母

材质: 304,316
直径: M6-M20



锥形螺帽(TONG标)

材质: 304
直径: M6 M8 M10 M12
牙别: 粗牙



卡式螺帽(TONG标)

材质: 304
直径: M4 M5 M6 M8
牙别: 粗牙



欧标滑块螺母 20型

材质: 304
直径: M4-M5



欧标滑块螺母 30型

材质: 304
直径: M4-M8



欧标滑块螺母 40型

材质: 304
直径: M4-M8



欧标滑块螺母 45型

材质: 304
直径: M4-M8



欧标弹片螺母 20型

材质: 304
直径: M3-M5



欧标弹片螺母 30型

材质: 304
直径: M4-M8



欧标弹片螺母 40型

材质: 304
直径: M5-M8



欧标弹片螺母 45型

材质: 304
直径: M6-M8



欧标弹珠螺母 20型

材质: 304
直径: M3-M5



欧标弹珠螺母 30型

材质: 304
直径: M4-M8



欧标弹珠螺母 40型

材质: 304
直径: M5-M8



欧标弹珠螺母 45型

材质: 304
直径: M6-M8



GB806 滚花高螺母

材质: 304
直径: M3-M10
牙别: 粗牙



DIN929 无焊点(TONG标)

材质: 304
直径: M4-M12
牙别: 粗牙



DIN928 B型(TONG标)

材质: 304
直径: M4-M10
牙别: 粗牙



圆柱螺母 (TONG标)

材质: 304
直径: M3-M25
牙别: 粗牙



美标 K帽

材质: 304+420
直径: 4#-5/16



DIN315 (THE标)

材质: 304, 316
直径: M3-M12
牙别: 粗牙



欧标T型螺母 20型

材质: 304
直径: M3-M5
牙别: 粗牙



欧标T型螺母 30型

材质: 304
直径: M3-M6
牙别: 粗牙



欧标T型螺母 40型

材质: 304
直径: M4-M8
牙别: 粗牙



欧标T型螺母 45型

材质: 304
直径: M4-M8
牙别: 粗牙

管法兰专用



HG/T20634 化工螺母

材质: 304,316

直径: M12-M48

牙别: 粗牙、细牙



UNI5587 加厚六角螺帽

材质: 304

直径: M27、M30

牙别: 粗牙



ANSIB18.2.2 重型双倒角

材质: 304、316

直径: 1/4-7/8

牙别: 粗牙



ANSIB18.2.2 重型单倒角

材质: 304、316、316L

直径: 1/2-2

牙别: 粗牙、等距螺纹UN-8

圆螺母



GB810

材质: 304、316

直径: M10-M200

牙别: 细牙、极细牙



GB812

材质: 304、316

直径: M10-M200

牙别: 细牙、极细牙



GB6181 开槽螺母

材质: 304

直径: M8-M20

垫圈 / 挡圈



WASHER / BEZEL

平垫



DIN125 A型

材质: 304,316,316L,2205,321
直径: M1.6-M64



DIN9021 加大

材质: 304,316,316L,2205
直径: M2.5-M30



DIN7349 重型

材质: 304,316
直径: M3-M24



GB848 小平垫

材质: 304,316
直径: M1.6-M36



GB5287 特大

材质: 304,316
直径: M5-M24



GB95 C级

材质: 304,316
直径: M1.6-M36



GB97.1 (200-300HV)

材质: 304,316
直径: M3-M42



GB96.1 (200-300HV)

材质: 304,316
直径: M4-M24



ANSIB18.22.1 SAE窄型

材质: 304,316
直径: 6#-2



ANSIB18.22.1 USS宽型

材质: 304,316
直径: 1/4-1



DIN433

材质: 304
直径: M3-M20



GB97.2 A级倒角型

材质: 304,316
直径: M5-M30



GB97.3 销轴用平垫圈

材质: 304
直径: M4-M10



NFE25-513 L系列(大)平垫

材质: 304,316
直径: M3-M20



定制平垫 (现货)

材质: 304
直径: M4-M30
厚度: 1mm-3mm



GB9074.24

材质: 304
直径: M2-M12

弹垫



GB93 标准型

材质: 304,316,316L
直径: M1.6-M52



DIN127 B型

材质: 304,316
直径: M2-M36



GB859 轻型

材质: 304
直径: M2-M27



ANSI B18.21.1 美标

材质: 304,316
直径: 4#-1



JIS B1251 日标

材质: 304
直径: M3-M30



GB7244 重型

材质: 304,316
直径: M6-M24



GB9074.26

材质: 304
直径: M2-M12

齿垫



GB861.1 内齿

材质: 304
直径: M2.5-M20



GB861.2 内锯齿

材质: 304
直径: M2.5-M20



GB862.1 外齿

材质: 304,316
直径: M2.5-M20



GB862.2 外锯齿

材质: 304,316
直径: M2.5-M20



DIN6797 J内齿

材质: 304
直径: M3-M20



DIN6797 A外齿

材质: 304
直径: M3-M20



DIN6798 J内锯齿

材质: 304
直径: M3-M24



DIN6798 A外锯齿

材质: 304
直径: M3-M24



DIN6798 V锥形锯齿

材质: 304
直径: M3-M16

挡圈



GB893.1 孔用(内卡)

材质: 304
直径: M6-M70



GB894.1 轴用(外卡)

材质: 304,316
直径: M6-M70



GB896 开口挡圈

材质: 304
直径: M2-M15

花色垫圈



GB853 槽钢用方斜垫圈

材质: 304,316
直径: M6-M30



NFE25-511 法标碟形压花
(宽型、窄型、中型)

材质: 304,316
直径: M3-M20



DIN9250 S系列双面斜印花

材质: 304
直径: M3-M20



DIN137 A鞍形弹性垫圈

材质: 304
直径: M2-M20



DIN137 B波形弹性垫圈

材质: 304
直径: M3-M20



GB860 鞍形弹性垫圈

材质: 304
直径: M2-M20



DIN6796 碟形垫圈

材质: 304,316
直径: M3-M24



SN70093 接地垫圈

材质: 304
直径: M3-M20



GB854 单耳止动垫圈

材质: 304,316
直径: M4-M48



GB855 双耳止动垫圈

材质: 304,316
直径: M4-M48



GB856 外舌止动垫圈

材质: 304,316
直径: M4-M48



GB852 工字钢用方斜垫圈

材质: 304,316
直径: M6-M36



DIN25201 双叠自锁垫圈

材质: 304,316
直径: M3-M30



DIN988 配合垫圈

材质: 304,316
直径: M3-M30

螺钉系列



SCREW SERIES

内六角螺钉



DIN912

材质: 304,316,316L
直径: M1.4-M30 长度: 3-270
牙别: 全牙、半牙



DIN7984 薄头内六角

材质: 304,316
直径: M3-M12 长度: 10-70
牙别: 全牙



DIN7991 沉头

材质: 304,316
直径: M2-M16 长度: 3-100
牙别: 全牙



ISO7380 盘头

材质: 304,316
直径: M2-M12 长度: 3-150
牙别: 全牙



ASMEB18.3 圆柱杯头

材质: 304,316
直径: 1/4-3/4 长度: 1/2-6
牙别: 全牙、半牙



GB70.1 无滚花

材质: 304
直径: M1.6-M8 长度: 2-100
牙别: 全牙

机螺钉



GB818 盘头

材质: 304,316
直径: M1-M12 长度: 2-120
牙别: 全牙



GB819 沉头

材质: 304,316
直径: M1-M12 长度: 3-120
牙别: 全牙



GB820 半沉头

材质: 304,316
直径: M2-M12 长度: 4-100
牙别: 全牙



GB823 小盘头

材质: 304,316
直径: M2-M12 长度: 3-100
牙别: 全牙



GB65 开槽圆柱头

材质: 304,316
直径: M1.6-M10 长度: 3-100
牙别: 全牙



GB67 开槽盘头

材质: 304,316
直径: M1.6-M10 长度: 3-100
牙别: 全牙



ANSIB18.6.3F 十字沉头

材质: 304,316
直径: 2#-12#, 1/4-3/8
长度: 5/32-4 牙别: 全牙



GB822 十字圆柱头

材质: 304,316
直径: M2.5-M8 长度: 3-100
牙别: 全牙



GB2672 梅花带柱

材质: 304
直径: M3-M8 长度: 4-100
牙别: 全牙



GB68 开槽沉头

材质: 304,316
直径: M1.6-M10 长度: 4-100
牙别: 全牙



GB2672 梅花盘头

材质: 304,316
直径: M2-M10 长度: 3-100
牙别: 全牙



GB2673 梅花沉头

材质: 304,316
直径: M2-M10 长度: 3-120
牙别: 全牙



GB2673 梅花带柱

材质: 304
直径: M3-M8 长度: 4-100
牙别: 全牙



ISO7380 梅花带柱

材质: 304
直径: M3-M10 长度: 6-100
牙别: 全牙



DIN967

材质: 304
直径: M2-M8 长度: 3-100
牙别: 全牙



JISB1111T 大扁头机钉

材质: 304,316
直径: M2-M8 长度: 3-100
牙别: 全牙



GB29.2 十字四穴六角

材质: 304,316
直径: M3-M8 长度: 5-100
牙别: 全牙



ANSIB18.6.3P 十字盘头

材质: 304,316
直径: 2#-3/8
长度: 5/32-4 牙别: 全牙



内六角平头机螺钉

材质: 304
直径: M4-M10 长度: 4-60
牙别: 全牙



GB6560

材质: 304
直径: M3-M6 长度: 4-20
牙别: 全牙



GB6561

材质: 304
直径: M3-M5 长度: 4-20
牙别: 全牙



ISO7380-2 圆头带垫
 材质: 304
 直径: M3-M8 长度: 4-40
 牙别: 全牙



ANSI/ASMEB 18.3BT 内六角平圆头
 材质: 304
 直径: 2#-3/8 长度: 5/32-4
 牙别: 全牙



ANSI/ASMEB 18.3F 内六角沉头
 材质: 304
 直径: 2#-3/8
 长度: 5/32-4 牙别: 全牙



DIN7985
 材质: 304
 直径: M2-M10 长度: 3-100
 牙别: 全牙



DIN965
 材质: 304
 直径: M1.6-M10 长度: 3-100
 牙别: 全牙



GB6560 三角牙螺钉
 材质: 304
 直径: M3 M4 M5 M6
 长度: 4-20 牙别: 全牙

自攻钉



GB845 盘头
 材质: 304,316,410
 直径: ST2.2-ST6.3
 长度: 4.5-100 牙别: 全牙



GB846 沉头
 材质: 304,316,410
 直径: ST2.2-ST6.3
 长度: 4.5-100 牙别: 全牙



JISB1122T 大扁头自攻
 材质: 304,316
 直径: ST2.2-ST6.3
 长度: 4.5-100 牙别: 全牙



DIN7982 沉头
 材质: 304
 直径: ST2.2-ST6.3
 长度: 4.5-100 牙别: 全牙



GB845 平尾
 材质: 304
 直径: ST2.2-ST6.3
 长度: 4.5-100 牙别: 全牙



GB846 平尾
 材质: 304
 直径: ST2.2-ST6.3
 长度: 4.5-100 牙别: 全牙



DIN968
 材质: 304
 直径: ST2.9-ST6.3
 长度: 6.5-100 牙别: 全牙



DIN7976
 材质: 304
 直径: ST2.9-ST6.3
 长度: 6.5-100 牙别: 全牙



GB16824.1
 材质: 304
 直径: ST2.2-ST9
 长度: 4.5-100 牙别: 全牙



内六角自攻钉
 材质: 304
 直径: ST2-ST6.3
 长度: 5-90 牙别: 全牙



内六角沉头自攻钉
 材质: 304
 直径: ST3-ST6
 长度: 4-60 牙别: 全牙



内六角平尾自攻钉
 材质: 304
 直径: ST3-ST6
 长度: 6-60 牙别: 全牙



DIN7981

材质: 304
直径: ST2.2-ST6.3
长度: 4.5-100 牙别: 全牙



DIN7982

材质: 304
直径: ST2.2-ST6.3
长度: 4.5-100 牙别: 全牙



GB13806.2B

材质: 304
直径: ST2.2-ST6.3
长度: 4.5-100 牙别: 全牙



GB13806.2A

材质: 304
直径: ST2.2-ST6.3
长度: 4.5-100 牙别: 全牙



GB2670.1

材质: 304
直径: ST2.2-ST6.3
长度: 4.5-100 牙别: 全牙



GB2670.2

材质: 304
直径: ST2.2-ST6.3
长度: 4.5-100 牙别: 全牙

粤标机螺丝



YB818 粤标盘头

材质: 304,316
直径: M2-M10 长度: 3-100
牙别: 全牙



YB819 粤标沉头

材质: 304,316
直径: M2-M10 长度: 3-100
牙别: 全牙



TM (粤标)十字大扁头

材质: 304,316
直径: M2-M10 长度: 4-80
牙别: 全牙



PWM (粤标)十字盘头带垫

材质: 304
直径: M3-M6 长度: 4-100
牙别: 全牙

粤标自攻钉



YB845 粤标盘头

材质: 304,316
直径: ST2-ST8
长度: 4-100 牙别: 全牙



YB846 粤标沉头

材质: 304,316
直径: ST2-ST8
长度: 5-100 牙别: 全牙



TA (粤标)十字大扁头

材质: 304,316
直径: ST3-ST6
长度: 6-100 牙别: 全牙



YB845 (粤标)十字盘头平尾

材质: 304
直径: ST2-ST6.3
长度: 4-50 牙别: 全牙



YB846 (粤标)十字沉头平尾

材质: 304
直径: ST2-ST6.3
长度: 5-30 牙别: 全牙



PWA (粤标)十字盘头自攻带垫

材质: 304
直径: M3 长度: 6-16
牙别: 全牙



YB846 平尾割尾

材质: 304

直径: ST2-ST6.3

长度: 4.5-100 牙别: 全牙



YB845 平尾割尾

材质: 304

直径: ST2-ST6.3

长度: 4.5-100 牙别: 全牙

木牙螺钉



DIN571 木牙

材质: 304, 316

直径: M6-M12 长度: 25-200

牙别: 木牙半牙



ANSI B18.2.1 美标木牙

材质: 304, 316

直径: 1/4-1/2 长度: 1-6

牙别: 木牙全牙, 木牙半牙

钻尾系列



DRILL TAIL SERIES

自攻自钻(钢牙螺丝)



华夫头钻尾

材质: 304,316,410,300系+400系复合
直径: ST5,ST5.5
长度: 13-50 牙别: 细牙



DIN7504N 盘头

材质: 304,316,410,300系+400系复合
直径: M3.5-M6.3
长度: 9.5-300



DIN7504P 沉头

材质: 304,316,410,300系+400系复合
直径: M3.5-P6.3
长度: 9.5-300



DIN7504K 六角法兰

材质: 304,316,410,300系+400系复合
直径: M3.5-M6.3
长度: 9.5-300



GB15856.1 盘头

材质: 304,316,410,300系+400系复合
直径: M3.5-M6.3
长度: 9.5-300



GB15856.2 沉头

材质: 304,316,410,300系+400系复合
直径: M3.5-M6.3
长度: 9.5-300



GB15856.4 六角法兰

材质: 304,316,410,300系+400系复合
直径: M4.2-M6.3
长度: 9.5-300



国标华威头钻尾

材质: 304,316,410,300系+400系复合
直径: M4.2
长度: 9.5-100



美标六角钻尾

材质: 304,316,410,300系+400系复合
直径: M6.3
长度: 16-300

组合螺丝



COMBINE SCREWS

小螺丝组合



GB9074.4 盘头

材质: 304,316
直径: M2-M8
长度: 6-60



GB9074.8 小盘头

材质: 304,316
直径: M2-M8
长度: 6-60



GB9074.13 四穴六角

材质: 304,316
直径: M3-M8
长度: 6-60



GB2672 梅花盘头三组合(THE标)

材质: 304
直径: M3-M8
长度: 6-50



GB9074.4 盘头小平垫组合

材质: 304
直径: M2.5 M3 M4
长度: 6-20



GB9074.8 小盘头小平垫组合

材质: 304
直径: M2.5 M3 M4
长度: 6-20



GB9074.3 十字盘头弹垫组合

材质: 304
直径: M2.5-M6
长度: 6-50



GB9074.7 十字槽小盘头弹垫组合

材质: 304
直径: M2.5-M6
长度: 6-50

内外六角组合



DIN912 平弹垫三组合

材质: 304,316
直径: M3-M16 长度: 6-150
牙别: 全牙



GB9074.17 外六角组合

材质: 304,316
直径: M4-M20 长度: 8-200
牙别: 全牙



ISO7380 三组合(THE标)

材质: 304
直径: M4-M8
长度: 6-100



DIN912 弹垫二组合

材质: 304,316
直径: M4-M16 长度: 6-150
牙别: 细杆半牙、全牙

膨胀系列



EXPANSION SERIES

膨胀螺丝(TONG标)



小头有缝膨胀螺丝

材质: 304,316,1803
直径: M6-M16
长度: 50-200



大头无缝膨胀螺丝

材质: 304,316
直径: M6-M16
长度: 50-200



不锈钢车修壁虎

材质: 304,316
直径: M6-M16
长度: 50-200



不锈钢内迫壁虎

材质: 304,316
直径: M6-M20
长度: 25-80



碳钢车修壁虎

材质: 普通碳(镀白锌)
直径: M6-M20
长度: 40-280



碳钢内迫壁虎

材质: 普通碳(镀白锌)
直径: M6-M20
长度: 25-80



鱼型膨胀管

材质: 尼龙(PA66)、聚乙烯(PE)
直径: M4-M16
长度: 20-80



外六角长眼内膨胀

材质: 304
直径: M6-M12
长度: 40-150



十字沉头长眼内膨胀

材质: 304
直径: M6-M10
长度: 40-120



内六角长眼内膨胀

材质: 304
直径: M6-M12
长度: 40-150



通讯外六角内膨胀

材质: 304
直径: M12 长度: 60
牙别: 全牙



三片式壁虎

材质: 304,316
直径: M6-M12
长度: 48-63



小头有缝膨胀钩

材质: 304
直径: M6-M12



大头无缝膨胀钩

材质: 304
直径: M6-M12



化学锚栓

材质: 304,316
直径: M8-M30 长度:110-380
牙别: 粗牙



倒锥化学锚栓

材质: 304,316
直径: M8-M30 长度: 110-380
牙别: 粗牙



化学锚栓药剂

直径: M8-M30
长度: 110-380



背栓

材质: 304,316
直径: M6,M8 长度: 25,32
牙别: 粗牙



无缝内膨胀

材质: 304
直径: M6-M12
长度: 40-150



内六角沉头长眼膨胀

材质: 304,316
直径: M6-M10
长度: 40-120



机械锚栓

材质: 304,316
直径: M8-M12
长度: 60-200



水泥钉

材质: 410,304+410、普碳钢
直径: M6-M12,1/4-7/16
长度: 30-400



四片式重型壁虎膨胀管(分片式)

材质: 304,316
直径: M6-M12
长度: 40 48 58 78



四片式鱼鳞壁虎膨胀管(整体式)

材质: 304,316
直径: M6-M12
长度: 40 45 50 65

慧鱼膨胀



安全锚栓 DUOPOWER

材质: 尼龙 (PA66)
直径: 5-14
长度: 25-80



安全尼龙锚栓 UX

材质: 尼龙 (PA66)
直径: 5-14
长度: 30-75



安全尼龙锚栓 SX

材质: 尼龙 (PA66)
直径: 4-14
长度: 20-80



安全尼龙锚栓 S

材质: 尼龙 (PA66)

直径: 5-14

长度: 25-75

喉塞／紧定



THROAT PLUG / TIGHT

喉塞



DIN906 内六角喉塞

材质: 304
直径: 1/6-1



DIN908 内六角圆柱头喉塞

材质: 304
直径: 1/8-30



DIN910 外六角喉塞

材质: 304
直径: 1/8-30

内六角紧定(止付螺丝)



DIN916 凹端

材质: 304, 316
直径: M2-M16 长度: 2-60
牙别: 全牙



DIN913 平端

材质: 304, 316
直径: M2-M16 长度: 2-60
牙别: 全牙



DIN914 尖端

材质: 304, 316
直径: M3-M16 长度: 3-50
牙别: 全牙



ANSI18.3 美标平端

材质: 304
直径: 8#-1/2
长度: 5/32-1 牙别: 全牙



ANSI18.3 美标凹端

材质: 304
直径: 8#-1/2
长度: 5/32-1 牙别: 全牙

销键/螺套/钢珠



PIN / KEY / SCREW SLEEVE

开口销



GB91

材质: 304、316
直径: M1-M10
长度: 8-120



DIN11024 弹性开口销(TONG标)

材质: 304
直径: M2.5-M7
长度: 12.5-97



封口销 (TONG标)

材质: 304
直径: M3-M5
长度: 23-33



R型开口销 (TONG标)

材质: 304
直径: M1.2-M3.5
长度: 21-75



B型开口销 (TONG标)

材质: 304
直径: M1.2-M3.5
长度: 21-75

圆柱销



圆柱销GB119.1 M6等级

材质: 303、316
直径: M3-M8
长度: 8-40



圆柱销GB119.1 H8等级

材质: 303
直径: M2-M8
长度: 8-40



GB879 弹性圆柱销

材质: 304
直径: M1.5-M8
长度: 5-80



GB879.4 标准型卷制弹性圆柱销

材质: 304
直径: M2-M6
长度: 6-50

定位销



定位销TPF(TONG标)

材质: 303
直径: M3-M6
长度: 8-20

钢丝螺套



DIN8140 有尾

材质: 304
直径: M2-M12
牙别: 全牙



302型开槽型自攻螺套

材质: 304
直径: M2-M16
牙别: 粗牙



307型三孔型自攻螺套

材质: 303
直径: M3-M16
牙别: 粗牙



插销螺套

材质: 303
直径: M2-M12
牙别: 粗牙



308型三孔型自攻螺套(TONG标)

材质: 303
直径: M3-M12
牙别: 全牙

键类



GB1096 普通平键A型

材质: 304
直径: M3-M12
长度: 8-60

钢珠



钢珠

材质: 304
直径: M1-M22.4



双头/牙条/U型栓

DOUBLE HEAD / TOOTH STRIP / U-BOLT

双头螺柱



GB901 等长双头B级

材质: 304,316
直径: M6-M24
长度: 40-300 牙别: 粗牙



GB901 倒角 等双头螺柱B级

材质: 304,316
直径: M6-M24
长度: 40-300 牙别: 粗牙



GB897 A级/GB898 A级

材质: 304
直径: M10-M20
长度: 25-200

牙条/牙棒



DIN976

材质: 304,316
直径: M3-M48
长度: 1M,2M,3M 牙别: 全牙



IFI136

材质: 304,316
直径: 10#,1/4-1
长度: 1M 牙别: 全牙



DIN976 双倒角牙棒

材质: 304
直径: M6-M64
长度: 30-500 牙别: 粗牙

U型栓



U型栓(TONG标)

材质: 304
直径: M6-M24

铆接系列



RIVETING SERIES

抽芯铆钉



GB12618 开口平圆头

材质: 304, 316, 304+42A(半钢)
直径: M3-M5
长度: 6-30



GB12617 开口沉头

材质: 304, 304+42A(半钢)
直径: M3-M5
长度: 6-25



GB12615 封闭平圆头

材质: 304, 316, 304+420
直径: M3.2-M6.4
长度: 6-40



GB12616 封闭沉头

材质: 304, 304+420
直径: M3.2-M4.8
长度: 6-20



单鼓抽芯铆钉

材质: 304
直径: M3.2-M4.8
长度: 6-18



双鼓抽芯铆钉

材质: 304
直径: M3.2-M4.8
长度: 8-18



海马抽芯铆钉

材质: 304
直径: M4.8, M6.4
长度: 1-18.5



拉丝抽芯铆钉(外锁)

材质: 304
直径: M4.8, M6.4
长度: 10-19



拉丝抽芯铆钉(内锁)

材质: 304
直径: M4.8, M6.4
长度: 10-19



GB827 标牌铆钉

材质: 304
直径: M2-M4
长度: 3-12



GB867

材质: 304
直径: M2-M8
长度: 3-30



GB869

材质: 304
直径: M2-M8
长度: 3-30

常规定制铆螺母



开口圆柱小沉头 似GB17880.3

材质: 304, 316, 碳钢
直径: M3-M12 牙别: 粗牙
长度: 10-19, 22.5mm



开口圆柱平头 似GB17880.1

材质: 304, 316, 碳钢, 铝合金6053
直径: M3-M12 牙别: 粗牙
长度: 8.8-19, 24.3mm



开口圆柱沉头 似GB17880.2

材质: 304, 316, 碳钢
直径: M3-M12 牙别: 粗牙
长度: 9.5-19, 22.5mm



开口半六角小沉头 似GB17880

材质: 304, 碳钢
直径: M4-M12 牙别: 粗牙
长度: 10-19



开口半六角平头 似GB17880

材质: 304, 碳钢
直径: M3-M12 牙别: 粗牙
长度: 13-20.3



封闭圆柱小沉头

材质: 304, 碳钢
直径: M4-M12 牙别: 粗牙
长度: 1-33



封闭圆柱平头

材质: 304、碳钢
直径: M4-M12 牙别: 粗牙
长度: 17.3-34.3mm



封闭圆柱大沉头

材质: 304、316、碳钢
直径: M4-M12 牙别: 粗牙
长度: 17.3-26.5mm



封闭半六角小平头

材质: 304、碳钢
直径: M4-M12 牙别: 粗牙
长度: 23、26.5



封闭半六角平头

材质: 304
直径: M4-M12
牙别: 粗牙



压铆螺母

材质: 304、410
直径: M3-M8 长度: 1-3
牙别: 粗牙



齐平螺母(片型螺母)

材质: 304
直径: M3-M6 长度: 1-4
牙别: 粗牙



BS05 盲孔压铆螺母柱

材质: 304
直径: M3-M5 长度: 6-30
牙别: 粗牙



压铆螺丝

材质: 304、316
直径: M3-M8
长度: 6-30

压铆系列



HAND SCREWS

蝶形



DIN315 (THE标)

材质: 304, 316
直径: M3-M12
牙别: 粗牙



蝶形螺丝 (THE标) 似DIN316

材质: 304
直径: M3-M12 长度: 8-50
牙别: 粗牙

滚花螺母



GB806 滚花高螺母

材质: 304
直径: M3-M10
牙别: 粗牙

内外螺纹间隔柱 (TONG标)



阴阳螺丝

材质: 304
直径: M3, M4 长度: 7-30
牙别: 粗牙

索具 / 喉箍



ROPE / THROAT HOOPS

索具(TONG标)



DIN580 吊丝

材质: 304,316
直径: M6-M42
牙别: 粗牙



DIN582 吊母

材质: 304,316
直径: M6-M24
牙别: 粗牙



钢丝绳卡头

材质: 304
直径: M2-M24
牙别: 粗牙



封闭花兰

材质: 304
直径: M5-M16
牙别: 粗牙



开口花兰OC型

材质: 304
直径: M4-M24
牙别: 粗牙



卸扣

材质: 304
直径: M4-M20
牙别: 粗牙



转环

材质: 304
直径: M4-M24
牙别: 粗牙



GB62.1 圆翼碟形螺母

直径: M6-M16
牙别: 粗牙



钢丝绳

材质: 304,316
直径: M0.8-M20
长度: 50M,300M



单夹

材质: 304
线径: 2mm-10mm



双夹

材质: 304
线径: 2mm-10mm



弹簧钩

材质: 304
规格: M4-M14



欧式套环

材质: 304
规格: 2mm-24mm



方形门扣

材质: 304
规格: 5mm,6mm,8mm



圆形门扣

材质: 304
规格: 5mm,6mm,8mm



椭圆形门扣

材质: 304
规格: 5mm,6mm,8mm



蛋扣

材质: 304
规格: 30mm,40mm,50mm、
70mm,100mm



菱形门扣

材质: 304
规格: 5mm,6mm,7mm



链条

材质: 304
直径: M1.2-M16
长度: 100m-1000m



万向钩

材质: 304
规格: 0#, 1#, 2#, 3#



活结/活节

材质: 304
直径: M5-M27
长度: 20-200



销轴 (TONG标)

材质: 304
直径: M3-M20
长度: 8-150

喉箍



美式 8mm带宽(小美)

材质: 304, 316
紧固: 8-30
长度: 12-29



美式 12.7mm带宽(大美)

材质: 304, 316
紧固: 11-300
长度: 25-305



德式 9mm带宽

材质: 304, 316
紧固: 8-200
长度: 12-200



德式 12mm带宽

材质: 304, 316
束紧: 16-200
长度: 25-160



强力喉箍

材质: 304
束紧: 17-140
长度: 19-148



扎带 (TONG标)

材质: 304
直径: 100-800



管卡 (TONG标)

材质: 304
直径: 5-110



胶条卡箍 (TONG标)

材质: 304
直径: 6-46

进口/共营系列



CO-PRODUCTION PRODUCTS

弹性圆柱销(进口)



JISB2808

材质: 304, 420

直径: M1-M6

长度: 4-50

HARD-LOCK 螺母



锁紧螺母

材质: 304, S45C碳钢, SS400碳钢

直径: M6-M30

牙别: 粗牙

双叠自锁垫圈(进口)



双叠自锁垫圈

材质: 304

直径: NL3-NL30SPSS

YAHATA日本进口



JISB1176 内六角螺钉 日本进口

材质: TW340日本钛合金
直径: M3-M8 长度: 6-50
牙别: 全牙、粗牙半牙自攻螺纹



JISB1180 外六角螺丝 日本进口

材质: TW340日本钛合金
直径: M6-M10 长度: 10-40
牙别: 全牙



JISB1181 外六角螺帽 日本进口

材质: TW340日本钛合金
直径: M3-M12
牙别: 粗牙



JISB1177 凹端紧定 日本进口

材质: 304
直径: M2-M12 长度: 2-50
牙别: 全牙

抽芯铆钉



GB12617 (铝铁)

材质: 5050/1008(铝铁)
直径: M3-M5
长度: 6-40



GB12617 (全铁)

材质: 08A/45A(全铁)
直径: M3-M5
长度: 6-40



GB12618 (铝铁)

材质: 5050/1008(铝铁)
直径: M3-M6.4
长度: 6-40



GB12618 (全铁)

材质: 08A/45A(全铁)
直径: M3-M6.4
长度: 6-40

日本进口产品



日本进口平键(一端圆形)

材质: 316、S45C碳钢
直径: M2-M12
长度: 8-100



日本进口平键(两端圆形)

材质: 304、316、S45C碳钢
直径: M2-M12
长度: 8-100



日本进口平键(两端方形)

材质: 316、S45C碳钢
直径: M2-M12
长度: 8-100



六星槽低头螺钉

材质: 304、铁
直径: M2-M6
长度: 4-40



C型孔用挡圈

材质: 304
直径: M6.4-M92



C型轴用挡圈

材质: 304
直径: M3.2-M95



E型开口挡圈

材质: 304
直径: M0.8-M24



JIS1168 吊环螺栓

材质: 304、316、SS400碳钢
直径: M6-M24
牙别: 粗牙



JIS1169 吊环螺帽

材质: 304、316、SS400碳钢
直径: M8-M24
牙别: 粗牙



外六角螺栓 似DIN933

材质: 尼龙(PA66)、聚丙烯(PP)、
聚乙烯(PVC)
直径: M3-M20 长度: 6-150
牙别: 粗牙



内六角机螺钉 似GB70.1

材质: 尼龙(PA66)、聚丙烯(PP)、
聚乙烯(PVC)
直径: M4-M10 长度: 6-60
牙别: 粗牙



十字盘头机螺钉 似GB818

材质: 尼龙(PA66)、聚丙烯(PP)、
聚乙烯(PVC)
直径: M2-M10 长度: 4-60
牙别: 粗牙



十字沉头机螺钉 似GB819

材质: 尼龙(PA66)、聚丙烯(PP)、
聚乙烯(PVC)
直径: M2-M20 长度: 4-60
牙别: 粗牙



外六角螺帽 似DIN934

材质: 尼龙(PA66)、聚丙烯(PP)、
聚乙烯(PVC)
直径: M3-M24
牙别: 粗牙



平垫 似DIN125

材质: 尼龙(PA66)、聚丙烯(PP)、
聚乙烯(PVC)
直径: M3-M20
牙别: 粗牙

塑料产品

其他产品



OTHERS

铜产品



DIN933

材质: 56铜、62铜
直径: M3-M48



DIN934

材质: 56铜、62铜
直径: M1.6-M64



GB6170

材质: 56铜、62铜
直径: M4-M39



DIN439

材质: 56铜、62铜
直径: M2-M20



GB809 镶嵌螺母

材质: 59铜
直径: M2-M5



内外螺纹间隔柱

材质: C3604铜
直径: M3、M4



DIN125

材质: 铜
直径: M2-M36



GB823

材质: 铜
直径: M2-M10
长度: 3-100



DIN985

材质: 62铜
直径: M4-M12



GB819

材质: 铜
直径: M2-M10
长度: 3-100



GB818

材质: 56铜、62铜
直径: M3-M8
长度: 4-100



GB93

材质: 紫铜
直径: M3-M20

持续更新中.....

TONG 東明
TONG MING ENTERPRISE

小成本 **锁无忧** 大保障



= 零锁死

高效防锁

多次实验验证“零锁死”

国家专利

获国家发明专利及铁道部检测认可
专利号(ZL 2013 2 0555013.6)

成本低廉

综合成本上升微乎其微

客户认可

管道阀门、高铁等锁死高发客户多年使用“零锁死”

清洁环保

通过欧盟ROHS环保认证

钢的类别	钢的组别	性能等级	抗拉强度 R ^a m/Mpa	规定塑性延伸率 为0.2%时的应力 R ^a p0.1/MPa min	断后伸长量 A ^b /mm min
奥氏体	A1、A2、A3、A4、A5	50	500	210	0.6d
		70	700	450	0.4d
		80	800	600	0.3d
a 按螺纹公称应力截面积计算。 b 按7.2.4规定测量的实际长度。					

抗拉扭矩

规格	安全扭矩 (单位: N.m)
M6-1.0	9
M8-1.25	20
M10-1.5	40
M12-1.75	55
M14-2.0	100
M16-2.0	150
M18-2.5	180
M20-2.5	220
M22-2.5	400
M24-3.0	510

安全扭矩



破坏扭矩



螺纹规格d	破坏扭矩 M_a , min/ (N·m)		
	性能等级		
	50	70	80
M1.6	0.15	0.2	0.24
M2	0.3	0.4	0.48
M2.5	0.6	0.9	0.96
M3	1.1	1.6	1.8
M4	2.7	3.8	4.3
M5	5.5	7.8	8.8
M6	9.3	13	15
M8	23	32	37
M10	46	65	74
M12	80	110	130
M16	210	290	330

复合/组合垫圈



不锈钢+EPDM 复合垫圈

材质: 304, 316L
直径: 4.2-9.5



PVC环保垫圈

材质: 聚氯乙烯 (PVC)
直径: 5.5 6.3



GB9074.26 组合用弹垫

材质: 304, 316
直径: M2-M12



GB9074.24 组合用平垫

材质: 304, 316
直径: M2-M12



GB/T97.4S 组合用平垫

材质: 304
直径: M2-M5



GB/T97.4N 组合用平垫

材质: 304
直径: M4-M12



EPDM 单体垫圈

材质: EPDM
直径: 4.8 5.5 6.3



防风垫圈

材质: 304, EPDM
直径: 5.5 6.3



APS AUTOMOTIVE ENTERPRISE CO., LTD.
APS (XIAMEN) TRADE CO., LTD.

AFFORDABLE AFTERMARKET PRODUCTS

We're committed to excellence, and we guarantee our products will last. Everything we manufacture undergoes extensive testing and inspections to ensure you'll always receive the best from us.

Questions? Please contact us. We'll be happy to help.

Where great craftsmanship meets great price!

UNIT A, 2/F, NO.143-3 YUEHUA ROAD, HULI DISTRICT, XIAMEN, P. R. CHINA 361006

T E L: 86-136 1605 9105 / 86-0592-262 0070

E-Mail: KARL@AAPS.CN / AA@AAPS.CN

W E B: WWW.APSPART.COM

WWW.AAPS.CN

APSPARTS.EN.ALIBABA.COM



Wechat



WhatsApp



Web



Web